

# imageRUNNER 1643 Series

## Black-and-White | Compact | User-Friendly

Print up to 45 ppm (BW)

Scan in color and black and white

Print up to 8-1/2" x 14"

2,300-sheet maximum paper capacity

Small businesses and corporate workgroups depend on solutions that help maximize resources, boost productivity, and are easy to manage. The cost-efficient imageRUNNER 1643 Series can do all that, and more. With fast output, scanning, faxing,¹ and high reliability, the imageRUNNER 1643iF/1643i multifunction devices help you accomplish a lot in a small space. The imageRUNNER 1643P printer model offers fast and reliable printing.



### **WORKFLOW EFFICIENCY**

Whether you're a small business or part of a workgroup, the imageRUNNER 1643iF/1643i models can help boost operational efficiency. Scan and email documents or conveniently scan to/print from a USB memory stick. The ID Card Copy feature easily copies two-sided cards onto the same page. Extend your document management capabilities when you scan using the standard PDF (OCR) format. Mobile workers can print from compatible mobile devices. Application Library provides users with a unique, customized device experience.



### **SECURITY**

Safeguard information with the imageRUNNER 1643iF/1643i models' security features. Canon's uniFLOW solution lets users securely retrieve documents from a networked device after authentication. Standard security features include the ability to send encrypted PDFs and add a digital device signature to PDF files. These models also include technology to verify that the device, firmware, and applications initialize without tampering. TX Archiving automatically forwards a copy of a fax to an administrator-defined destination.1 And with no hard disks in these models, confidential information is not stored locally on the device.





## **QUALITY AND RELIABILITY**

With a first-copy-out time as fast as 6.3 seconds and output up to 45 ppm, the imageRUNNER 1643 Series is a quick performer. Scan documents in black and white and color to email addresses or networked locations. The 5" intuitive, color touchscreen display² has smartphone-like usability. The standard 650-sheet capacity can be increased to 2,300 sheets to handle many jobs without interruption.



### **FLEET MANAGEMENT**

An ideal replacement for single-function printers or older models, the imageRUNNER 1643 Series can easily integrate into your network of Canon devices to help streamline and simplify management and maintenance. Even receive alerts when supplies or service calls are needed with imageWARE Enterprise Management Console and plug-ins.



### **EFFICIENT PERFORMANCE**

Designed with your bottom line in mind, the Canon imageRUNNER 1643 Series helps minimize costs and maximize reliability while the robust design helps ensure dependable operation. Canon's uniFLOW\* software can help control costs by managing, tracking, and charging back usage. And simple-to-replace, high-yield consumables help keep work moving while achieving a low cost per page.



### **SUSTAINABILITY**

The imageRUNNER 1643 Series is ENERGY STAR\* certified and has a low TEC (Total Energy Consumption) rating. Rated EPEAT\* Silver,³ these models follow Canon's stringent Green Procurement policy and environmental commitments.











<sup>\*</sup> Can add up to three additional cassettes. It's strongly suggested to have Cabinet Type-S when utilizing two or three cassette configurations.

## **SPECIFICATIONS**

### Main Unit

Type

1643iF/1643i: Monochrome Laser Multifunctional 1643P: Monochrome Laser Printer

Core Functions

1643iF: Print, Copy, Scan, Send, Fax 1643i: Print, Copy, Scan, Send

1643P: Prir

Processor

Canon Dual Custom Processor<sup>2</sup> (Shared)

**Operation Panel** 

1643iF/1643i: 5" TFT LCD WVGA Color Touch Panel

1643P: 5-Line LCD Panel

Memory 1.0 GB RAM

Interface Connection<sup>4</sup>

Network 1643iF/1643i: 1000Base-T/100Base-TX/10-(Standard): Base-T, Wireless LAN (IEEE 802.11 b/g/n),

NFC, Wi-Fi Direct Connection 1643P: 1000Base-T/100Base-TX/10-Base-T

Others 1643iF/1643i: USB 2.0 (Host) x2, USB 2.0

(Standard): (Device) x1

1643P: USB 2.0 (Host) x3, USB 2.0 (Device) x1

Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette, 100-sheet Stack Bypass

Optional: 550-sheet PAPER FEEDER PF-C1 (up to 3)

Maximum: 2,300 Sheets

Paper Output Capacity (LTR, 20 lb. Bond)

Maximum: 150 Sheets **Supported Media Sizes** 

Cassette: Letter, Legal, Statement, Executive Bypass: Letter, Legal, Statement, Executive,

Custom size (3" x 5" to 8-1/2" x 14"), Envelope (C5/DL/ COM-10/Monarch)

Supported Media Weights

Cassette: 16 lb. Bond to 32 lb. Bond  $(60 \text{ to } 120 \text{ g/m}^2)$ Bypass: 16 lb. Bond to 73 lb. Cover  $(60 \text{ to } 199 \text{ g/m}^2)$ 

Copy Speed<sup>2</sup>/Print Speed Up to 45 ppm (Letter);

Up to 36 ppm (Legal)
Warm-up Time

From Power On: **1643iF/1643i:** 14 Seconds or Less<sup>5</sup>

1643P: 30 Seconds or Less<sup>5</sup>
From Sleep
Mode: 1643iF/1643i: 4 Seconds or Less
1643P: 3 Seconds or Less

Dimensions (W x D x H)

1643iF: 19-7/16" x 18-5/16" x 17-3/16"

(494 mm x 465 mm x 452 mm) 18-7/8" x 15-5/16" x 17-13/16"

(480 mm x 465 mm x 452 mm) 1643P: 16-1/8" x 14-13/16" x 10-13/16"

(409 mm x 376 mm x 275 mm)

Installation Space (W x D)

1643iF: 27-7/8" x 43-1/2" (708 mm x 1105 mm) 1643i: 27-5/16" x 43-1/2" (694 mm x 1105 mm) 1643P: 24-5/16" x 43-7/16" (617 mm x 1104 mm)

 $\textbf{Weight}^{6}$ 

1643i:

1643iF/1643i: Approx. 41.9 lb. (19 kg) 1643P: Approx. 25.3 lb. (11.5 kg)

**Print Specifications** 

First-Print-Out Time (LTR) Approx. 5.7 Seconds

Print Resolution (dpi)

600 × 600

Standard Page Description Languages

UFR II LT, PCL®5e/6, Adobe® PS® 3 (Standard on 1643iF/1643P,

optional on 1643i)

Optional: Barcode Printing Kit

**Direct Print Support** 

Supported File TIFF, JPEG, PDF and XPS (only LPR)
Types: Available from USB memory, LPR

Print Features

Suspend Job Timeout, Profile Settings, Secure Print, Header/ Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Front/ Back Covers, Toner Reduction, Poster Printing

Operating System

1643iF/ Windows 10/8.1/7 (32/64 bit), Windows 1643i/1643P: Server (2019/2016/2012 R2 (64 bit)/2012 (64 bit)/ 2008 R2 (64 bit)/2008 (32/64

bit), Mac\* (OS X 10.6 and later => 10.9 ~ 10/14) Linux (Web Distribution)

Drivers

1643iF/ UFR II, PCL 5/6, Adobe PS 3 (Standard 1643i/1643P: on 1643iF/P and optional on 1643i)

Copy Specifications (1643iF/1643i Only)

First-Copy-Out Time (LTR)

As fast as 6.0 Seconds (via Platen)

Copy Resolution (dpi)

Reading/

Printing: Up to 600 x 600 Copy Specifications

Automatic or Manual (9 Levels)

**Multiple Copies** Up to 999

Magnification

25% - 400% (1% Increments) from Platen Glass

Preset Reductions 25%, 50%, 64%, 78% Preset Enlargements

129%, 200%, 400% Basic Copy Features

Preset R/E Ratios by Area, Paper Setting, Favorite Setting, Two-Sided, Density Adjustment, Original Type Selection

Special Copy Features

Two-sided Original, Sort, Job Build, N on 1, Different Size Originals, Density Adjustment, Original Type Selection,

Sharpness, Erase Frame, Copy ID Card

Scan Specifications (1643iF/1643i Only)

Type

Single Pass Duplexing Automatic Document Feeder

**Document Feeder Paper Capacity** 

LTR: 50 Sheets (20 lb. Bond), LGL: 30 Sheets (20 lb. Bond)

Maximum Original Size

Up to 8-1/2" x 14"

Document Feeder Supported Media Sizes

4-1/8" x 5" to 8-1/2" x 14"

**Document Feeder Supported Media Weights**Simplex: 13 lb. to 28 lb. Bond (50 to 105 g/m²)

luplex: 17 lb. to 28 lb. Bond (64 to 105 g/m²)

**Platen Acceptable Originals** Sheet, Book, 3-Dimensional Objects

Network TWAIN Scan

Standard

**Network Scan Utility** ScanGear MF

Scan Resolution (dpi) Up to 600 x 600

Scan Speed (LTR)

300 dpi

Simplex: Up to 38ipm (BW)/ 13ipm (Color)
Duplex: Up to 70ipm (BW)/ 26 (Color)

600 dpi

Simplex: Up to 21 ipm (BW) Duplex: Up to 35 ipm (BW) Send Specifications (1643iF/1643i Only)

Destination

E-mail/Internet FAX (SMTP), SMB, FTP

Color Mode Color, BW

Scan Resolution (dpi)

600 dpi, 300 dpi (CL/BW)

Address Book

LDAP (50)/Local (300)/Speed Dial (281)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP)

Email: SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF(Compact, Searchable,

Encrypted, Digital Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Density
Adjustment, Sharpness, File Name, Subject/Message,
E-mail Priority, TX Report, Original Content Orientation

Fax Specifications (1643iF Only)

Maximum Number of Connection Lines

One

Modem Speed Super G3: 33.6 Kbps G3: 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Letter, Legal, Statement, Executive

Fax Features

Two-sided Original, Density (for Scanning), Sharpness, TX Report, RX Mode, Resolutions, Favorite Settings

Store Specifications

Memory Media

Standard: USB

**Security Specifications** 

Authentication

Standard: 1643iF/1643i: Department ID, Embedded

Universal Login Manager, uniFLOW Online

Express<sup>7</sup>

1643P: Department ID

802.1X, IPv6

Optional: 1643iF/1643i/1643P: uniFLOW and uniFLOW

Online

Network Standard:

 d: 1643iF/1643i: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0,

IEEE 802.1X, IPv6, SMTP Authentication, POP

Authentication before SMTP 1643P: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE

Document

Standard: 1643iF/1643i: Secure Print, Encrypted PDF,

Device Signature 1643P: Secure Print

## **Environmental Specifications**

**Power Requirements** 120-127 V, 60 Hz, 7.1 A

**Power Consumption** 

Maximum: 1643iF/1643i: Approx. 1430W

1643P: Approx. 1370W Sleep Mode: 1643iF/1643i: 0.9 W8 1643P: 1.9 W<sup>9</sup>

Typical Electricity Consumption (TEC) Rating<sup>10</sup>

1643iF/1643i: 0.40 kWh 1643P: 0.50 kWh

Plug (Main Unit) NEMA 5-15P Standards

ENERGY STAR® Certified Rated EPEAT® Silver

## Paper Supply Options

PAPER FEEDER PF-C1

Paper

550 Sheets [20 lb. Bond (80 g/m<sup>2</sup>)] Capacity: Thin, Plain, Thick, Color, Recycled, Bond Paper Type:

ITR IGL STMT FXF Paper Size:

Custom Size: 4-1/8" x 5-7/8" to 8-1/2" x 14" (105.0 mm x 148.0mm to 216.0 mm x 355.6

Paper Weight: 16 lb. Bond to 32 lb. Bond (60 to 120 g/m<sup>2</sup>)

Power Source: From the Main Unit 18-7/8" x 18-1/4" x 33-1/8" Dimensions (480 mm x 464 mm x 842 mm)11  $(W \times D \times H)$ :

Weight: 8.8 lb. (4 kg)

**CABINET TYPE-S** 

20-15/16" x 20-9/16" x17" Dimensions (532 mm x 522 mm x 432 mm)  $(W \times D \times H)$ :

33.07 lb. (15 kg) Weight:

## Other Options

1643iF/1643i/1643P:

USB Keyboard

Universal Keyboard Stand-A1

Card Reader Assembly for Universal Keyboard Stand

Convenience Stapler-Á1

1643iF/1643i:

ADF Access Handle-A1 Copy Control Interface Kit-C1 Barcode Printing Kit-E1 MiCard Attachment Kit-B1

1643i:

PS Printer Kit-CB1

1643P:

Barcode Printing Kit-F1 SD card-C1 PCL Font Set-C1 SX-BR-4600WAN

## Consumables

#### Toner Yield

20,500 Images

(Estimated Yield @ ISO 19752 Coverage) NOTE: Toner not included in the main unit.

- 1 imageRUNNER 1643iF model only.
- <sup>2</sup> Applies to imageRUNNER 1643iF/1643i models only.
- <sup>3</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- imageRUNNER 1643P model does not have direct connection capabilities, and does not come standard with Wi-Fi. Time from device power-on until copy ready
- (not print reservation).
- <sup>6</sup> Includes consumables
- <sup>7</sup> No charge for this solution, however activation is required.
- 8 0.9 W Sleep mode not available in all circumstances due to certain settings.
- 9 1.9 W Sleep mode not available in all circumstances
- due to certain settings.

  Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.
- 11 Attached to Main Unit.

NOTE: Check for availability and details for uniFLOW solutions.















As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or of your devices and data. Print speed is based on internal testing. Print speed may vary depending on the number of copies selected, as well as on the settings for size, type, and orientation of paper. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2019 Canon U.S.A., Inc. All rights reserved.





