

imageRUNNER ADVANCE DX C359iF C259iF

Environmental Profile Sheet

Canon's imageRUNNER ADVANCE DX C359iF/C259iF models incorporate technologies with a strong environmental focus at every stage of the product lifecycle–Produce, Use, and Recycle. The technologies listed below focus on Energy Conservation, Resource Conservation, and Pollution Prevention and form the foundation of Canon's Environmental Management System.

	Energy Conservation	Resource Conservation	Pollution Prevention
In order to help reduce dependence on petroleum-based materials, Canon uses 100% reused plastics .*		1	
A variety of sleep recovery triggers help encourage the use of Sleep Mode , helping to minimize power consumption.	1		
Power consumption in Sleep Mode is as low as 0.80 W!	1		
Low Typical Electricity Consumption (TEC) values, which measure power consumption during a one-week period.	1		
Power consumption is reduced by utilizing White LED array technology in its Color Image Reader versus using a traditional Xenon tube!	1		
RAPID Fusing technologies help reduce power consumption and limit the warm-up period .	1		
Low Melting Temperature Toner helps reduce fusing temperature requirements.	1		
All suppliers are required to meet Canon's stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union's RoHS Directive, which controls/restricts the use of certain hazardous substances .			1
Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources .	1	1	
Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle.		Ĵ	1

* Excluding a small amount of additives to improve physical properties.

Canon. The Natural Partner for Business.







imageRUNNER ADVANCE DX C359iF

imageRUNNER ADVANCE DX C359iF shown with Cassette Feeding Unit-AJ1

Environment-Related Specifications

System Type

Color Laser Multifunctional

Functions		
Standard:	Print (UFR III, PCL® 6, Adobe® PostScript® 3"), Copy, Scan, Send, Store, Fax	
Optional:	Fax (Second line)	
Operation Panel	10.1" TFT LCD WSVGA Color Flat-panel	
Warm-up Time		
From Power On:	Approx. 10 Seconds	
From Sleep Mode:	Approx. 10 Seconds	
Quick Startup Mode:	Approx. 4 Seconds	
Power Requirements	110-127 V AC, 60 Hz, 6.9 A	
Power Consumption		
Maximum:	1,500 W	
Sleep Mode:	0.80 W	
Copying/Printing:	528 W	
Plug-in:	0.40 W	
One Week TEC:	C359iF: 0.32 kWh C259iF: 0.21 kWh	
One Year TEC:	C359iF: 16.6 kWh C259iF: 10.9 kWh	
British Thermal Units (BTU)		
Maximum (BTU/Hr.):	5,119	
Copying/Printing (BTU/Hr.):	1,802	

* Including consumables.

** 1[B] = 10[dB].

Plug

*** Measured in accordance with ISO7796. Presented in accordance with ISO9296.

NEMA 5-15P

Percentage based on weight of recycled content. ⁺ The percentage of plastics the device contains that's derived from recycled plastic

materials (by weight).

⁺⁺ The percentage of reused waste material.

*** The percentage of recycled PETE material.

ENERGY STAR, TEC Values, and EPEAT is based off of ENERGY STAR version 3.0.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks of the EPA. PostScript® 3™ is either a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. PCL 6 is a trademark of Hewlett Packard Company. Canon, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2023 Canon U.S.A., Inc. All rights reserved.

05/23-0861-8411

Dimensions (W x D x H)

20-1/2" x 25-7/8" x 25-1/8" (519 mm x 658 mm x 638 mm)

Installation Space (W x D)

Basic: 33-1/2" x 35-3/4" (852 mm x 908 mm) With Staple Finisher-Z1: 55-3/8" x 35-3/4" (1407 mm x 908 mm)

Weight*	Approx. 108 lb. (49 kg)		
Noise Levels (LwA,m [B])**			
Standby:***	0.8 B		
Copying/Printing***	Color	Black and White	
C359iF:	5.3 B	5.3 B	
C259iF:	5.1 B	4.9 B	
Recycled Content			
Recycled Primary Package (%):■	Approx. 23.7%		
Post-consumer Waste:*	0.10%		
Secondary Waste Materials:**	0.0%		
Recycled PETE Product:***	0.0%		
Recycled Paper Support			

100% Post-consumer Content: Yes

Environmental Standards Compliance

ENERGY STAR® Certified

EPEAT[®] Gold

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer







