













Environmental Profile Sheet

Canon's imageRUNNER ADVANCE DX 717iF/717iFZ/617iF/617iFZ/527iF/527iFZ models incorporate those technologies with a strong environmental focus at every stage of the product life cycle—Produce, Use, and Recycle. The technologies listed below focus on Energy Conservation, Resource Conservation, and Pollution Prevention and form the foundation of Canon's Environmental Management System.

	Energy Conservation	Resource Conservation	Pollution Prevention
In order to help reduce dependence on petroleum-based materials, Canon uses 100% recycled plastics .*			
A variety of sleep recovery triggers, including motion sensing, help encourage the use of Sleep Mode , helping to minimize power consumption.			
Power consumption in Sleep Mode is as low as 0.41 W!			
Low Typical Electricity Consumption (TEC) values , which measure power consumption during a one-week period.			
Power consumption is reduced by utilizing White LED array technology in its Color Image Reader versus using a traditional Xenon tube!			
RAPID Fusing technologies help reduce power consumption and limit the warm-up period .			
EF Toner, with its low melting point, helps reduce fusing temperature requirements .			
All suppliers are required to meet Canon's stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union's RoHS Directive, which controls/restricts the use of certain hazardous substances .			
Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources .			
Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle.			

* Excluding a small amount of additives to improve physical properties.

Canon. The Natural Partner for Business.



imageRUNNER ADVANCE DX 717iF and 717iFZ shown.

Environment-Related Specifications

System Type

Monochrome Laser Multifunctional

Functions

Standard: Print (UFR III, PCL® 6, Adobe® PostScript® 3™),
Copy, Scan, Send, Store, Fax

Operation Panel

10.1" TFT LCD WSVGA Color Flat-panel

Warm-up Time

From Power On:	Approx. 10 Seconds
From Sleep Mode:	Approx. 10 Seconds
Quick Startup Mode:	Approx. 4 Seconds

Power Requirements: 110-127 V AC, 60 Hz, 9.7 A

Power Consumption Maximum: 1,500 W

Sleep Mode: Standard Model: 0.51
Finisher Model: 0.41

Copying/Printing:

717iF: 905 W; 617iF: 864 W; 527iF: 789 W

717iFZ: 945 W; 617iFZ: 896 W; 527iFZ: 876 W

Copy Ready (Standby): Standard Model: 28 W
Finisher Model: 30 W

Plug-in: 0.40 W

One Week TEC: 717iF/717iFZ: 0.84 kWh
617iF/617iFZ: 0.69 kWh
527iF/527iFZ: 0.58 kWh

One Year TEC: 717iF/717iFZ: 0.84 kWh
617iF/617iFZ: 0.69 kWh
527iF/527iFZ: 0.58 kWh

British Thermal Units (BTU)

Maximum (BTU/Hr.): 5,119

Copying/Printing (BTU/Hr.)

717iF: 3,087 717iFZ: 3,224
617iF: 2,950 617iFZ: 3,056
527iF: 2,692 527iFZ: 2,989

Copy-Ready (Standby) (BTU/Hr.): Standard Model: 94
Finisher Model: 102

Plug: NEMA 5-15P

Dimensions (W x D x H)

Standard Model:
19-3/4" x 23-1/2" x 24-1/4" (500 mm x 598 mm x 617 mm)

Finisher Model:
19-3/4" x 23-1/2" x 32-1/8" (502 mm x 598 mm x 814 mm)

Installation Space (W x D)

41-3/8" x 32-3/8" (1,052 mm x 823 mm)

Weight*

Standard Model: Approx. 81.6 lb. (37 kg)
Finisher Model: Approx. 101.4 lb. (46 kg)

Noise Levels (LwA,m [B])**

Standby:*** Standard Model: 3.4 B
Finisher Model: 3.8 B

Copying/Printing:*** Standard Model: 94 B
Finisher Model: 102 B

Recycled Content

Recycled Primary Package (%):** Standard Model: Approx. 25%
Finisher Model: Approx. 27%

Post-consumer Waste:*** Standard Model: Approx. 0.27%
Finisher Model: Approx. 0.21%

Secondary Waste Materials:† 0.0%

Recycled PETE Product:†† 0.0%

Recycled Paper Support

100% Post-consumer Content: Yes

Environmental Standards Compliance ENERGY STAR® Certified
EPEAT® Gold

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer

* Includes Main Unit, ADF, and Consumables.

** 1[B] = 10[dB].

*** Measured in accordance with ISO7796. Presented in accordance with ISO9296.

† Percentage based on weight of recycled content.

† The percentage of plastics the device contains that's derived from recycled plastic materials (by weight).

†† The percentage of reused waste material.

††† The percentage of recycled PETE material.

USA.CANON.COM/ENERGYSTAR

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks of the EPA. PostScript® 3™ is either a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. PCL 6 is a trademark of Hewlett Packard Company. Canon, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2020 Canon U.S.A., Inc. All rights reserved.

0720-DX717iFSEPS-PDF-IH

