

## imageRUNNER ADVANCE DX 719iF Series

**Black-and-white**  
**Compact**  
**Multifunction**

Print up to 75 ppm (BW)

Scan up to 200 ipm (300 dpi) (BW/color, duplex)

Print up to 8-1/2" × 14"

3,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



### WORKFLOW EFFICIENCY

- A large, 10.1" responsive and intuitive touchscreen with smartphone-like usability, making operation clear and virtually seamless.
- Consistent interface across the imageRUNNER ADVANCE DX product line, allowing work to proceed effortlessly and with a minimal learning curve.
- A unique, customized experience that can be tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.<sup>1</sup>
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Easily scan to, and print from, cloud services or email directly from the device User Interface.<sup>\*\*</sup>



### SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM\*<sup>2</sup> systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at setup. Includes automatic recovery of boot process for self resiliency.
- Trellix™ Embedded Control<sup>3</sup> utilizes whitelisting to help protect against malware and tampering of firmware and applications.
- Security settings can be established at once by selecting the environment type in Recommended Security Settings. Security policy settings can be configured from a central location and exported to other supported devices.
- Control access to the device and specific features using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>4</sup>



### QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

\* Security Information and Event Management  
 \*\* Optional Cloud Connector term license required.



## DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



## COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.<sup>5</sup>

## CONFIGURATION OPTIONS

imageRUNNER ADVANCE DX 719iF\*  
(Standard Model)



imageRUNNER ADVANCE DX 719iFZ  
(Finisher Model)



### CASSETTE FEEDING UNIT-AR1

- 550-sheet capacity and cabinet for storage
- Supports up to Legal
- Supports 60 to 135 g/m<sup>2</sup>



### CASSETTE FEEDING UNIT-AX1

- 1,650-sheet capacity
- Supports up to Legal
- Supports 60 to 135 g/m<sup>2</sup>



### HIGH CAPACITY CASSETTE FEEDING UNIT-D1

- 2,650-sheet capacity (550-sheet upper cassette, 2,100-sheet lower cassette)
- Supports up to Legal
- Supports 60 to 135 g/m<sup>2</sup>



### CASSETTE MODULE-AG1\*\*

- 550-sheet capacity
- Supports up to Legal
- Supports 60 to 135 g/m<sup>2</sup>

### ENVELOPE CASSETTE MODULE-A1<sup>▲</sup>

- 75-sheets (Envelope)
- Supports COM10 (No.10), Monarch, DL, ISO-C5
- Supports 80 to 100 g/m<sup>2</sup>



### CABINET TYPE-U<sup>▲▲</sup>

- Provides base (with wheels) for cassettes

\* Finisher cannot be added after purchase.

\*\* Floor standing configuration (not including Cabinet Type-U): "iF" models can add one optional cassette; "iFZ" models do not allow for any optional cassettes. Desktop configuration: "iF" models can add two optional cassettes; "iFZ" models can add one optional cassette.

▲ Maximum of two Envelope Cassette Module-A1 units can be configured, can be used as only the first or second additional cassette.

▲▲ Cabinet Type-U is required for the following configurations: "iF" models with two or more optional cassettes; "iFZ" models with one or more optional cassettes.

# SPECIFICATIONS

## Main Unit

### Type

Monochrome Laser Multifunction

### Core Functions

Print, Copy, Scan, Send, Fax

### Processor

1.8 GHz Dual Core Processor

### Control Panel

10.1" TFT LCD WSVGA Color Touch-panel

### Memory

Main CPU Side: 2 GB

Image Processing 1 GB + 512 MB

CPU Side:

### Solid State Drive

256 GB

### Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T

Optional: Wireless LAN Board-D1

Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)

Optional: Copy Control Interface

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 650 Sheets

Maximum: 3,200 Sheets

### Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette, 100-sheet  
Stack Bypass

Optional: 550-sheet (CASSETTE FEEDING UNIT-AR1),  
2,650-sheet (HIGH CAPACITY CASSETTE  
FEEDING UNIT-D1), 550-sheet (CASSETTE  
MODULE-AG1), 75-envelope (ENVELOPE  
CASSETTE MODULE-A1)

### Paper Output Capacity (LTR, 20 lb. Bond)

Standard Model: 500 Sheets

Finisher Model: 1,000 Sheets

### Finishing Capabilities

Standard Model: Collate, Group

Finisher Model: Collate, Group, Offset, Staple

### Supported Media Types

Cassettes: Thin, Plain, Recycled, Color, Heavy,  
Labels, Bond, Pre-punched

Multi-purpose: Thin, Plain, Recycled, Color, Heavy,  
Tray: Transparency, Bond, Envelope

### Supported Media Sizes

Cassette (Std.): Letter, Executive, Statement, Letterhead,  
Custom size (3-7/8" x 5-7/8" to 8-1/2" x 11-3/4")

Cassettes (Opt.): Legal, Letter, Executive, Statement, Letterhead,  
Custom size (3-7/8" x 5-7/8" to 8-1/2" x 14")

Multi-purpose: Legal, Letter, Executive, Statement, Envelope  
Tray: [No.10 (COM10), Monarch, DL, ISO-C5],  
Custom size (3" x 5" to 8-1/2" x 14")

### Supported Media Weights

Cassette: 16 lb. Bond to 36 lb. Bond (60 to 135 g/m<sup>2</sup>)

Multi-purpose: 16 lb. Bond to 53.3 lb. Cover (60 to 200 g/m<sup>2</sup>)

Tray:

Duplex: 16 lb. Bond to 32 lb. Bond (60 to 120 g/m<sup>2</sup>)

### Print/Copy Speed (BW)

719iF/719iFZ: Up to 75 ppm (Letter);  
Up to 59 ppm (Legal)

619iF/619iFZ: Up to 65 ppm (Letter);  
Up to 51 ppm (Legal)

529iF/529iFZ: Up to 55 ppm (Letter);  
Up to 45 ppm (Legal)

### Warm-up Time

From Power On: 10 Seconds or Less<sup>6</sup>

On:

From Sleep

Mode: 10 Seconds or Less<sup>7</sup>

Quick Startup

Mode: 4 Seconds or Less<sup>8</sup>

### Dimensions (W x D x H)

Standard Model: 19-3/4" x 23-1/2" x 24-1/4"  
(500 mm x 598 mm x 617 mm)

Finisher Model: 19-3/4" x 23-1/2" x 32-1/8"  
(502 mm x 598 mm x 814 mm)

### Installation Space (W x D)

41-3/8" x 32-3/8" (1,052 mm x 823 mm) (with left CRG door  
open + right door open + the cassette drawer open)

### Weight<sup>9</sup>

Standard

Model: Approx. 81.6 lb. (37 kg)

Finisher Model: Approx. 101.4 lb. (46 kg)

## Print Specifications

### Print Resolution (dpi)

1200 x 1200 (equivalent)

### Standard Page Description Languages

UFR II, PCL<sup>®</sup> 6, Adobe<sup>®</sup> PS<sup>®</sup> 3

### Supported File Types

PDF, TIFF, JPEG, EPS, XPS

### Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based  
solutions (including Cloud Connector, AirPrint, Mopria,  
Universal Print by Microsoft<sup>®</sup>, Canon PRINT Business, and  
uniFLOW Online) are available to provide printing from  
mobile devices or internet-connected devices and cloud-  
based services depending on your requirements. Please  
contact your sales representative for further information.

### Fonts

PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T (Japanese,  
Korean, Simplified and Traditional  
Chinese),<sup>10</sup> Barcode Fonts<sup>11</sup>

PS: 136 Roman

### Operating System<sup>12</sup>

UFR II/PS: Windows<sup>®</sup> 8.1/10/11/Server 2012/Server  
2012 R2/Server 2016/Server 2019/Server  
2022, Mac OS X (10.12 or later)

PCL: Windows<sup>®</sup> 8.1/10/11/Server 2012/  
Server 2012 R2/Server 2016/Server 2019/  
Server 2022

PS: Windows<sup>®</sup> 8.1/10/11/Server 2012/Server  
2012 R2/Server 2016/Server 2019/Server  
2022, Mac OS X (10.12 or later)

PPD: Windows<sup>®</sup> 10/11, Mac OS X (10.12 or later)

## Copy Specifications

### First-Copy-Out Time (LTR)

As fast as 5 Seconds

### Copy Resolution (dpi)

600 x 600

### Multiple Copies

Up to 9,999

### Magnification

25%-400% (1% Increments)

### Preset Reduction/Enlargement

25%, 50%, 64%, 78%, 100% (1:1), 129%, 200%, 400%

## Scan Specifications

### Type

Single-pass Duplexing Automatic Document Feeder<sup>13</sup>

### Document Feeder Paper Capacity

Up to 100 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

Legal, Letter, Statement

Custom Size: 1-7/8" x 5" to 8-1/2" x 14" (48.0 mm x 128.0  
mm to 216.0 mm x 355.6 mm)

Business Card: 1-7/8" x 3-3/8" to 2-1/8" x 3-5/8" (48.0 mm  
x 85.0 mm to 55.0 mm x 91.0 mm)

### Document Feeder Supported Media Weights

Single-sided 13.3 lb. Bond to 34 lb. Bond (50 to 128 g/m<sup>2</sup>)

Scanning: (BW), 17 to 34 lb. bond (64 to 128 gsm) (CL)

Double-sided 13.3 lb. Bond to 34 lb. Bond (50 to 128 g/m<sup>2</sup>)

Scanning: (BW), 17 lb. Bond to 34 lb. Bond (64 to  
128 g/m<sup>2</sup>) (CL)

Business Card: 21.3 lb. Bond to 80 lb. Cover (80 to 220 g/m<sup>2</sup>)

Card:

### Platen Maximum Scanning Size

Up to 8-1/2" x 14" (216.0 mm x 355.6 mm)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects

### Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows<sup>®</sup> 7/8.1/10/Server 2008/Server 2008  
R2/Server 2012/Server 2012 R2/Server 2016

### Scan Resolution (dpi)

Scan for Copy: 600 x 600

Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/  
IFAX), (Pull) 600 x 600

Scan for Fax: 600 x 600

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning  
to compatible mobile devices or cloud-based services  
depending on your requirements.

### Scan Speed (LTR)

Send (300 x 300 dpi)

Automatic Color Select "OFF"

Single-sided

Scanning: 100

Double-

sided

Scanning: 200

Automatic Color Select "ON"

Single-sided

Scanning: 50

Double-

sided

Scanning: 100

Copy (600 x 600 dpi)

Single-sided

Scanning: 100

Double-

sided

Scanning: 155

## Send Specifications

### Destination

Standard: Email/Internet Fax (SMTP), SMB,  
FTP, WebDAV, Mail Box

Optional IP Fax, Super G3 Fax

### Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

### Scan Resolution (dpi)

Push: Up to 600 x 600

Pull: Up to 600 x 600

### Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV

Email: SMTP, POP3

### File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable,  
Apply Policy, Optimize for Web, PDF  
A/1-b, Trace & Smooth, Encrypted, Device  
Signature, User Signature), XPS (Compact,  
Searchable, Device Signature, User  
Signature), Office Open XML (PowerPoint,  
Word)

## Fax Specifications

### Maximum Number of Connection Lines

One

### Modem Speed

Super G3: 33.6 Kbps  
G3: 14.4 Kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution (dpi)

400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)

### Sending/Recording Size

Statement to Legal

### Fax Memory

Up to 30,000 Pages (2,000 Jobs)

### Speed Dials

Max. 200

### Group Dials/Destinations

Max. 199 Dials

### Sequential Broadcast

Max. 256 Addresses

### Memory Backup

Yes

## Store Specifications

### Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored (2,000 Jobs)

### Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows 8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB

## Security Specifications

### Authentication

Standard: Universal Login Manager (Device and Function Level Log-in), User Authentication, Department ID Authentication, Access Management System, uniFLOW Online Express<sup>14</sup>  
Optional: uniFLOW

### Data

Standard: Protecting SSD Data (SSD Data Encryption (FIPS140-2 Validated, SSD Lock), SSD Data Overwrite Erase, SSD Lock), Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Checking MFP Software Integrity (Verify System at Startup, Runtime Intrusion Detection with Trellix Embedded Control), Common Criteria Certification (IEEE2600.2/HCD-PP)  
Optional: IEEE 2600 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Space in the MFP, Scan and Send-Virus Concerns for E-mail Reception

### Document

Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print<sup>15</sup>), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle<sup>®</sup> Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86 °F  
Humidity: 20 to 80% RH (Relative Humidity)

### Power Requirements

110-127V, 60 Hz, 9.7 A

### Plug (Main Unit)

NEMA 5-15P

### Power Consumption

Maximum: Approx. 1,500 W

Sleep Mode: Approx. 1.0 W<sup>16</sup>

Typical Electricity Consumption (TEC) Rating<sup>17</sup>

iR-ADV DX 529iF: 0.55 kWh

iR-ADV DX 529iFZ: 0.55 kWh

iR-ADV DX 619iF: 0.66 kWh

iR-ADV DX 619iFZ: 0.66 kWh

iR-ADV DX 719iFZ: 0.79 kWh

iR-ADV DX 719iFZ: 0.79 kWh

### Standards

ENERGY STAR<sup>®</sup> Certified

Rated EPEAT<sup>®</sup> Gold<sup>5</sup>

## Consumables

### Toner

T03 Black (All-in-One Toner Cartridge)<sup>18</sup>

### Toner Yield

51,500 images @ ISO 19752

<sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.

<sup>2</sup> Third-party SIEM system required. Subject to third-party SIEM system Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.

<sup>3</sup> This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.

<sup>4</sup> Requires additional option.

<sup>5</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).

<sup>6</sup> Time from device power-on until copy ready (not print reservation).

<sup>7</sup> Time from exiting sleep mode to when printing is operational.

<sup>8</sup> Time from device power-on to when copy icon appears on the main menu of touch-panel.

<sup>9</sup> Includes consumables.

<sup>10</sup> Requires the optional PCL International Font Set-A1.

<sup>11</sup> Requires the optional Barcode Printer Kit-D1.

<sup>12</sup> Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>13</sup> Detect Feeder Multi Sheet Feed is supported.

<sup>14</sup> No charge for this solution; however, activation is required.

<sup>15</sup> Requires uniFLOW Online/uniFLOW.

<sup>16</sup> 1.0 W Sleep mode not available in all circumstances due to certain settings.

<sup>17</sup> Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

<sup>18</sup> Includes toner, drum, developer, and waste toner hopper.

AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Trellix and the Trellix logo are trademarks or registered trademarks of Musarubra US LLC or its subsidiaries in the U.S. and other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
©2023 Canon U.S.A., Inc. All rights reserved.

# Canon

USA.CANON.COM/SIMPLYADVANCED



## Trellix

CANON  
GENUINE  
TONER, CARTRIDGE  
& PARTS



To learn about Canon's many awards, visit  
[usa.canon.com/awards](http://usa.canon.com/awards).