

Environmental Profile Sheet

The imageFORCE C3150 incorporates technologies with a strong environmental focus at every stage of the product lifecycle—Produce, Use, and Recycle. The technologies below focus on Energy Conservation, Resource Conservation, and Pollution Prevention and form the foundation of Canon's Environmental Management System.

	Energy Conservation	Resource Conservation	Pollution Prevention
In order to help reduce dependence on petroleum-based materials, Canon uses 100 percent reused plastics .*			
A variety of sleep recovery triggers help encourage the use of Sleep Mode , helping to minimize power consumption.			
Power consumption in Sleep Mode is as low as 0.50 W! **			
Low Typical Electricity Consumption (TEC) values , which measure power consumption during a one-week period.			
Lower Melting Temperature Toner helps reduce fusing temperature requirements .			
Lighter products and easy foldable cardboard packaging. Continuing development of product and packaging design to reduce the impact of transportation and logistics .			
Designed with sustainability efforts in mind, 30% of the resin material *** is made with recycled plastic material – increased from 2% on the conventional Canon office MFP.			
All suppliers are required to meet Canon's stringent Green Procurement policy and environmental terms. This helps Canon exceed the tough European Union's RoHS Directive, which controls/restricts the use of certain hazardous substances .			
Each system is equipped with paper-, toner-, and energy-saving features that help to cut costs and conserve resources .			
Long-life parts and high-yield supplies help maximize uptime and help reduce the amount of materials consumed during the product life cycle.			

* Excluding a small amount of additives to improve physical properties.

** 0.5 W is not available in all circumstances due to certain settings.

***Resin materials are inclusive of device covers, cassettes, parts of the user interface and other plastic parts.

Canon. The Natural Partner for Business.



imageFORCE C3150 shown with optional Cassette Feeding Unit-AZ1, Booklet Finisher-AH1, and Paper Deck Unit-F3

imageFORCE C3150

imageFORCE C3150 Environmental Specs

System Type

OLED/A3 Color Multifunction

Functions

Standard: Print (UFR II, PCL® 6, Adobe® PostScript® 3™), Copy, Scan, Send, Store

Optional: Fax, Up to 2 lines

Operation Panel

10.1" TFT LCD WSVGA Color Touch panel

Warm-up Time

From Power On: Approx. 10 Seconds or less¹

From Sleep Mode: Approx. 10 Seconds or less²

Quick Startup Mode: Approx. 4 Seconds³

Power Requirements

110-127V, 60Hz, 12A

Power Consumption

Maximum: Approx. 1,800 W

Sleep Mode: Approx. 0.5 W⁴

Copying/Printing: 865 W

Plug-in: 0.40 W

One Week TEC:⁵ 0.5 kWh

One Year TEC:⁵ 26.0 kWh

British Thermal Units (BTU)

Maximum (BTU/Hr.): 6142 BTU/Hr

Copying/Printing (BTU/Hr.): 2952 BTU/Hr

Plug:

NEMA5-15P

Dimensions (W x D x H)

Standard (including 1-Pass DADF): 22-1/4" x 29-3/8" x 35-3/8" (565 x 745 x 897 mm)

Installation Space (W x D)

Basic: 38-1/2" x 44-7/8" (978 x 1,141 mm) (with right door & multi-purpose tray opened + paper cassette opened)

Fully Configured: 65" x 44-7/8" (1,651 x 1,141 mm) (with Staple Finisher-AH1/Booklet Finisher-AH1 + Copy Tray-T2 extended + paper cassette open)

Weight⁶

Approx. 200.6 lb (91 kg)

Noise Levels (LwA,m [B])⁷

Copying/Printing ⁸	Color	Black-and-White
imageFORCE C3150	6.7 B	6.6 B

Recycled Content

Recycled Primary Package (%)⁹ Approx. 48.0%

Recycled Paper Support

100% Post-consumer Content: YES

Environmental Standards Compliance

ENERGY STAR® certified
Achieved EPEAT Gold

Environment-conscious Features

Two-sided, Copy Sample, Confirmation/Cancel, Image Combination, ID Card Copy, Secured Print, Job Forwarding, Department ID Management, Access Management System, Authentication (Universal Login Manager), Standard Duplex Driver, Auto/Weekly Sleep Timer, Auto/Weekly Shutdown Timer, Staple-Free Stapling (Optional)

¹ Time from device power-on until copy ready (not print reservation).

² Time from exiting Sleep mode to when printing is operational.

³ Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.

⁴ 0.5 W is not available in all circumstances due to certain settings.

⁵ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.2.

⁶ Includes consumables.

⁷ 1[B] = 10[dB].

⁸ Measured in accordance with ISO7796. Presented in accordance with ISO9296.

⁹ Percentage based on weight of recycled content.



usa.canon.com/business